

PP25027JGY

Polypropylene Compound

Special Characteristics: PP25027JGY is a product of injection grade of PP 25% Talcum compound which is specially designed high flexural strength as well as suitable for automotive applications.

Typical Applications: Injection molded part.

Color: Grey(N755)

Typical Properties:

Properties	PP25027JGY	Unit	Test Method
Physical Properties			
Melt Flow Rate (230°C, 2.16 kg)	25	g/10 min	ISO 1133
Density	1.07	g/cm ³	ISO 1183
Mechanical and Thermal properties			
Tensile Strength at Yield	24	MPa	ISO 527
Elongation at Break	80	%	ISO 527
Flexural Strength	36	MPa	ISO 178
Flexural Modulus	2,700	MPa	ISO 178
Notched Izod Impact Strength at 23°C	8	kJ/m ²	ISO 180
Heat Deflection Temperature at 0.45 MPa	115	°C	ISO 75

Recommendation:

For injection molding

- Melt temperature: 190–240°C*
- Mold temperature: 45–65°C

* However, the actual processing conditions depend on mold design, power of machine, equipment, and other environments.

Disclaimer: To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however, we do not assume any liability whatsoever for the accuracy and completeness of such information. We make no warranties which extend beyond the description contained herein. Nothing herein shall constitute any implied warranty of merchantability or fitness for a particular purpose. It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products. No liability can be accepted in respect of the use of our products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

Note : Properties reported here are typical values of the product, not to be considered as specifications.
GC makes no representations as to the accuracy or completeness of the information contained herein.